

Sealed. Power.



When the Power Goes Off, We Power the World's Critical UPS Applications: Embassy

When you need a dependable, rechargeable, sealed maintenance-free battery for critical VRLA applications...you need the battery that the world turns to: Embassy. Powerful. Reliable. Providing a long service life in crucial applications.

**UPS & Power Management Systems • Security Systems • Medical Equipment
Railroad Systems • Renewable Energy • Telecommunications Installations**



The advanced technology that drives Embassy VRLA batteries is the technology that provides the power demands of people throughout the world. Power that makes life easier. Power that helps raise the standard of living, health and safety for many communities. Embassy...the perfect power solution.



SPECIFICATIONS

Model Number	BCI Group	Voltage	20 Hr Ah	Product Footnotes	Physical Specifications									
					Inches			Millimeters			Term. Height		Weight	
					L	W	H	L	W	H	in.	mm.	lbs.	kgs.
EMBASSY® AGM SERIES														
4CE4.5		4	4.5	T1	1.89	1.89	4.02	48	48	102	4.25	108	1.1	0.5
4CE10		4	10.0	T1	4.02	1.73	3.74	102	44	95	3.98	101	2.3	1.0
6CE1.2		6	1.2	T1	3.82	0.94	2.05	97	24	52	2.28	58	0.6	0.3
6CE3		6	3.0	T1	5.28	1.38	2.40	134	35	61	2.64	67	1.5	0.6
6CE5		6	5.0	T1	2.76	1.85	3.98	70	47	101	4.21	107	1.6	0.7
6CE7.5		6	7.5	T1	5.94	1.34	3.70	151	34	94	3.94	100	2.5	1.1
6CE8		6	8.0	T1	3.86	2.20	4.61	98	56	117	4.69	119	2.9	1.2
6CE12		6	12.0	T1, T2	5.94	1.97	3.70	151	50	94	3.94	100	4.2	1.8
6CE14		6	14.0	T3	4.25	2.80	5.51	108	71	140	5.51	140	5.2	2.2
6CE36		6	36.0	T2,B1	6.38	3.46	6.41	162	88	163	6.69	170	12.6	5.4
12CE1.2		12	1.2	T1	3.82	1.69	2.05	97	43	52	2.28	58	1.2	0.5
12CE2.3		12	2.3	T1	7.01	1.38	2.40	178	35	61	2.64	67	2.1	0.9
12CE3		12	3.0	T1	5.28	2.64	2.40	134	67	61	2.64	67	2.8	1.2
12CE5		12	5.0	T1	3.54	2.76	3.98	90	70	101	4.21	107	3.7	1.6
12CE7.5		12	7.5	T1,T2	5.94	2.56	3.70	151	65	94	3.94	100	4.8	2.1
12CE10	Scooter	12	10.0	T2	5.95	2.56	4.37	151	65	111	4.60	117	6.4	2.7
12CE12		12	12.0	T1,T2	5.94	3.86	3.74	151	98	95	3.98	101	8.0	3.4
12CE18		12	18.0	B1,T2	7.13	3.03	6.57	181	77	167	6.57	167	11.6	5.0
12CE21		12	21.0	M5	7.13	3.03	6.57	181	77	167	6.57	167	13.9	6.0
12CE21 W/C	UPS	12	21 Watts per cell	Recess	3.54	2.76	3.98	90	70	101	3.98	101	4.0	1.7
12CE26		12	26.0	B1,T2	6.50	6.93	5.00	165	176	127	5.00	127	17.1	7.4
12CE35	U1	12	35.0	J,H	7.68	5.12	6.10	195	130	155	7.09	180	22.3	9.6
12CE40		12	40.0	B2	7.76	6.50	6.73	198	165	171	6.73	171	28.6	12.3
12CE55	22NF	12	55.0	J	9.02	5.43	8.19	229	138	208	9.06	230	36.7	15.8
12CE75	24	12	75.0	J,M,H	10.20	6.61	8.31	260	168	211	9.06	230	49.3	21.2
12CE100	27	12	100.0	J,M,H	12.09	6.65	8.31	307	169	211	9.17	233	60.0	25.9
12CE110	31	12	110.0	M,H	12.91	6.77	8.50	328	172	236	9.29	236	67.3	29.0
EMBASSY® AGM MONOBLOC SERIES														
CE704	0809-0010	4	5.0	T2	3.81	2.13	3.02	97	54	77			1.46	0.66
CE705	0859-0010	4	8.0	T2	3.81	2.13	4.00	97	54	102			2.02	0.92
CE706	0809-0012	6	5.0	T2	5.48	2.13	3.02	139	54	77			2.16	0.98
CE707	0859-0012	6	8.0	T2	5.48	2.13	4.00	139	54	102			3.15	1.43
CE708	0818-0012	6	2.5	T1	4.48	1.81	2.75	114	46	70			1.15	0.52

Specifications are subject to change without notice.

Key

- | | |
|---|--|
| B1 = Nut & Bolt M5 | M5 = Inserted M5 Threaded Terminal |
| B2 = Nut & Bolt M6 | Recess = Recessed Positive T2, Recessed Negative T1 |
| H = Fitted with Handle | T1 = Quick Disconnect Tabs 0.187 in x 0.032 in |
| J = Heavy Duty Nut & Bolt | T2 = Quick Disconnect Tabs 0.250 in x 0.032 in |
| M = Threaded Stainless Steel Stud Terminal | T3 = Polarized Quick Disconnect Tabs |



1445 Majestic Drive
P.O. Box 990
Fremont, OH 43420-0990 USA
+1-419-334-7181
Fax +1-419-334-7124
www.crownbattery.com
sales@crownbattery.com